Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of the claims in the application:

Listing of Claims:

1. (original) A method comprising:

a keyboard scan engine integrated on a chipset initiating a keyscan process;

the keyboard scan engine detecting a key depression;

when in a trusted mode, transmitting a key code, corresponding to the key depression, through a trusted internal bus interface.

2. (original) The method of claim 1, wherein the trusted internal bus interface is a trusted Universal Serial Bus (USB) interface.

3. (currently amended) The method of claim 1, further including:

when in a non-trusted mode, sending a key code, corresponding to the key depression, through an interface to be processed by an onboard ~~key board~~ keyboard controller.

4. (currently amended) The method of claim 3, wherein, in the not-trusted mode, the key code is transmitted to the onboard ~~key board~~ keyboard controller via a PS/2 interface.

5. (currently amended) The method of claim 1, wherein ~~the a~~ the keyboard scan engine is integrated on ~~a I/O~~ an I/O hub controller of the chipset.

6. (original) The method of claim 5, wherein the I/O hub controller includes a port expander interfacing with a keyboard.

7. (original) The method of claim 5, wherein the keyboard scan engine implements a key scan algorithm.

8.   (original) A system comprising:

a central processing unit;

a memory unit; and

a keyboard scan engine integrated on a chipset, the keyboard scan engine to initiate a keyscan process, detect a key depression, and, when in a trusted mode, transmit a key code, corresponding to the key depression, through a trusted internal bus interface.

9.   (original) The system of claim 8, wherein the trusted internal bus interface is a trusted Universal Serial Bus (USB) interface.

10.   (currently amended) The system of claim 8, further including:

when in a non-trusted mode, the key code is to be transmitted through an interface to be processed by an onboard ~~key board~~ keyboard controller.

11.   (currently amended) The system of claim 10, wherein, in the not-trusted mode, the key code is to be transmitted to the onboard ~~key board~~ keyboard controller via a PS/2 interface.

12.   (currently amended) The system of claim 8, wherein ~~the a~~ the keyboard scan engine is integrated on ~~a I/O~~ an I/O hub controller of the chipset.

13.   (original) The system of claim 12, wherein the I/O hub controller includes a port expander interfacing with a keyboard.

14.   (original) The system of claim 12, wherein the keyboard scan engine implements a key scan algorithm.

15.   (currently amended) A machine-readable medium having stored thereon a set of instructions, which when executed by a processor, ~~performa~~ perform a method comprising:

a keyboard scan engine integrated on a chipset initiating a keyscan process;

the keyboard scan engine detecting a key depression;

when in a trusted mode, transmitting a key code, corresponding to the key depression, through a trusted internal bus interface.

16.   (original) The machine-readable medium of claim 15, wherein the trusted internal bus interface is a trusted Universal Serial Bus (USB) interface.

17.   (currently amended) The machine-readable medium of claim 15, further including:

when in a non-trusted mode, sending a key code, corresponding to the key depression, through an interface to be processed by an onboard ~~key board~~ keyboard controller.

18.   (currently amended) The machine-readable medium of claim 17, wherein, in the not-trusted mode, the key code is transmitted to the onboard ~~key board~~ keyboard controller via a PS/2 interface.

19.   (currently amended) The machine-readable medium of claim 15, wherein ~~the a~~ the keyboard scan engine is integrated on ~~a I/O~~ an I/O hub controller of the chipset.

20.   (original) The machine-readable medium of claim 19, wherein the I/O hub controller includes a port expander interfacing with a keyboard.

21.   (original) The machine-readable medium of claim 19, wherein the keyboard scan engine implements a key scan algorithm.

22.   (original) A system comprising:
        a central processing unit;
        a memory unit;
        a graphics controller; and

a keyboard scan engine integrated on a chipset, the keyboard scan engine to initiate a keyscan process, detect a key depression, and, when in a trusted mode, transmit a key code, corresponding to the key depression, through a trusted internal bus interface.

23.   (original) The system of claim 22, wherein the trusted internal bus interface is a trusted Universal Serial Bus (USB) interface.

24.   (currently amended) The system of claim 22, further including:
        when in a non-trusted mode, the key code is to be transmitted through an interface to be processed by an onboard key board keyboard controller.

25.   (currently amended) The system of claim 24, wherein, in the not-trusted mode, the key code is to be transmitted to the onboard key board keyboard controller via a PS/2 interface.

26.   (currently amended) The system of claim 22, wherein the a the keyboard scan engine is integrated on a I/O an I/O hub controller of the chipset.

27.   (original) The system of claim 26, wherein the I/O hub controller includes a port expander interfacing with a keyboard.